

SECADORES FRIGORÍFICOS



CODIGO	MODELO	CAUDAL	PRESIÓN	POTENCIA	ALIMENTACION	CONEXIÓN	DIMENSIONES	PESO
		l/min	Bar	W	Volt/Fases/Hz	gas/DIN	L W H mm.	Kg.
4102000740	DRY 20	333	16	130	230/MONO/50	3/4" M	350x500x450	19
4102000741	DRY 25	417	16	130	230/MONO/50	3/4" M	350x500x450	19
4102000742	DRY 45	750	16	164	230/MONO/50	3/4" M	350x500x450	19
4102000743	DRY 60	1.000	16	190	230/MONO/50	3/4" M	350x500x450	20
4102000744	DRY 85	1.417	16	266	230/MONO/50	3/4" M	350x500x450	25
4102000745	DRY 130	2.167	16	284	230/MONO/50	3/4" M	350x500x450	27
4102000746	DRY 165	2.750	13	609	230/MONO/50	1" H	370x500x764	44
4102000747	DRY 210	3.500	13	673	230/MONO/50	1" H	370x500x764	44
4102000748	DRY 250	4.167	13	793	230/MONO/50	1 1/2" H	460x560x789	53
4102000749	DRY 290	4.833	13	870	230/MONO/50	1 1/2" H	460x560x789	60
4102000750	DRY 360	6.000	13	1072	230/MONO/50	1 1/2" H	460x560x789	65
4102000751	DRY 460	7.667	13	1190	230/MONO/50	1 1/2" H	580x590x899	80
4102000752	DRY 530	8.833	13	1446	230/MONO/50	1 1/2" H	580x590x899	80
4102000975	DRY 690	11.500	13	1818	400/TRIF/50	2" H	735x898x962	128
4102000976	DRY 830	13.833	13	2013	400/TRIF/50	2" H	735x898x962	146
4102000977	DRY 1040	17.333	13	2636	400/TRIF/50	2" H	735x898x962	158
4102000978	DRY 1260	21.000	13	3568	400/TRIF/50	2" H	735x898x962	165

***CONDICIONES DE REFERENCIA. Presion trabajo: 7 bar / T° Aire Entrada: 35°C / T° Ambiente: 25°C / Pto. de Rocio 4-6°C

FACTOR DE CORRECCIÓN: F= A X B X C

_ Temperatura Ambiente	°C	25	30	35	40	45							
	A	1,00	0,92	0,84	0,8	0,74							
_ Temperatura de Ejercicio	°C	30	35	40	45	50	55						
	B	1,24	1,00	0,82	0,69	0,58	0,45						
_ Presión de Funcionamiento	bar (psi)	5(72)	6(87)	7(100)	8(116)	9(130)	10(145)	11(159)	12(174)	13(188)	14(203)	15(218)	16(232)
	C	0,9	0,96	1,00	1,03	1,06	1,08	1,10	1,12	1,13	1,15	1,16	1,17

ACCESORIOS OPCIONALES (PARA MODELOS DRY 20-130)

BY-PASS + SOPORTE FILTROS (No incluye Filtros)

CODIGO	MODELO	CONEXIÓN
		gas/DIN
4101000651	BY- PASS SOPORTE	3/4" M

SOPORTE FILTROS (No incluye Filtros)

CODIGO	MODELO	CONEXIÓN
		gas/DIN
4101000650	SOPORTE	3/4" M

